

INSTALLATION COMPONENTS

A range of miscellaneous components for use when installing Heat Trace products

MISCELLANEOUS ANCILLARIES




- Stainless steel pipe fixing straps in a range of 5 different sizes complete with buckle. Width of strap 12mm.
- PFS025/SS** Pipe fixing strap - for pipes up to 50mm (2") diameter.
 - PFS050/SS** Pipe fixing strap - for pipes from 50mm (2") to 125mm (5") diameter.
 - PFS100/SS** Pipe fixing strap - for pipes from 125mm (5") to 250mm (10") diameter.
 - PFS160/SS** Pipe fixing strap - for pipes from 250mm (10") to 450mm (18") diameter.
 - PFS200/SS** Pipe fixing strap - for pipes from 450mm (18") to 600mm (24") diameter.

Fixing Strap	Suitable for Pipe Sizes	Material	Length of Strap	Length of Slotted section
PFS025/SS	2"	SS304	320mm	160mm
PFS050/SS	2" - 5"	SS304	560mm	240mm
PFS100/SS	5" - 10"	SS304	960mm	400mm
PFS160/SS	10" - 18"	SS304	1600mm	800mm
PFS200/SS	18" - 24"	SS304	2075mm	1450mm

Dimension +/- 5%




- Cut to length metal pipe fixing straps with a continuous slotted section, available in either galvanised (G) or stainless steel (S).
- PFS/G or PFS/S** 30m x 11mm coil of banding supplied in dispensing box.
 - BUC/G or BUC/S** Buckles (1 x required for each fixing strap).




- SB/CMJB** Stainless steel support bracket for CMJB, CMAT, CMCT and CMCT/W's. Dimensions: 120mm x 120mm x 70mm height (approx).
- PB/S** Stainless steel pipe bracket for single component. (Junction box, or capillary thermostat etc.) Dimensions: 150mm x 150mm x 80mm height (approx).
- PB/M** Stainless steel pipe bracket for two components (subject to component size). Dimensions: 300mm x 200mm x 80mm height (approx).

(Other sizes available on request dependent on required quantities).



- LEK/U/FFG1** Lagging entry kits, protects heating cable when entering lagging and forms seal around cable entry to prevent water ingress. Refer to the termination method matrix for the appropriate kit for each cable.
- LEK/U/FFG3**
- LEK/U/FFG5** *(Kits supplied complete with aluminium plate, rubber seal, 4 self-tapping fixing screws, instruction card and FFG cable gland).*



- BP/JB9000** M20 Blanking plug (plastic). Can be provided for use in either SAFE or HAZARDOUS Areas.
- BP/JB9000/M25** M25 Blanking plug (plastic). Can be provided for use in either SAFE or HAZARDOUS Areas.




The Heat Tracing Authority™



We Believe there is Strength in Partnership

Thermal solutions and services for all applications to all industries.




BP/FL

M20 Blanking plug (brass).
Can be provided for use in either SAFE or HAZARDOUS Areas.

BP/FL/M25

M25 Blanking plug (brass).
Can be provided for use in either SAFE or HAZARDOUS Areas.



HBK

Insulating heat break. Used to protect pipe mounted components from exposure to excessive pipe surface temperatures.

Mineral wool base with silicone rubber sheet.

Dimensions: 130mm x 60mm x 35mm high.

Max Withstand Temperature: 250°C (approx).



CL

Self-adhesive, vinyl CAUTION / WARNING label for fixing to insulated pipework or vessel to indicate that electric heating cable is installed beneath the thermal insulation. To be fitted on pipework at intervals NOT exceeding 6 metres.

For large quantities in alternative languages, please enquire for details.



Heat Trace Ltd, Mere's Edge, Chester Road, Helsby, Frodsham, Cheshire, WA6 0DJ, England.

Tel: +44 (0)1928 726451

www.heat-trace.com

Email: info@heat-trace.com



HTUK Services Ltd, Alexandra Building, Wearfield, Sunderland, SR5 2TA

Tel: 0191 5166686

www.HTUK-Services.co.uk

Email: enquiries@ht-uk.com

The information given herein, including drawings, illustrations and schematics are intended for illustration purposes only. Heat Trace Ltd makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. Users of Heat Trace Ltd products should make their own evaluation to determine the suitability of each such product for specific applications. In no way will Heat Trace Ltd be liable for any damages arising out of the misuse, resale or use of the product.